

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A method for monitoring a process, the method comprising:

creating a signature representative of the process;

continuously updating the created signature; and

detecting abnormalities based upon the continuously updated signature[.]],

wherein the process is related to usage of networked computing devices in a datacenter, and

wherein the signature includes information related to time sensitive averaging that accounts for variation in a business cycle.

2. (Original) The method of claim 1, wherein creating a signature comprises calculating an average and a standard deviation.

3. (Original) The method of claim 2, wherein creating a signature comprises accelerated learning through incrementally increasing a learning responsiveness ratio.

4. (Original) The method of claim 2, wherein creating a signature comprises initially repeating a running average and standard deviation through a plurality of intervals.

5. (Original) The method of claim 1, wherein updating the created signature comprises using a weighting factor to ensure that recently recorded data has a greater impact than older data.

6. (Original) The method of claim 1, wherein updating the created signature comprises utilizing a moving average over a time to account for events occurring at unexpected times.

7. (Original) The method of claim 1, wherein detecting abnormalities comprises determining if measured values are above an upper threshold or below a lower threshold.

8. (Original) The method of claim 1, further comprising calculating upper and lower threshold limits based on jitter offset.

9. (currently amended) A computer ~~readable~~storage medium having computer executable instructions for performing the method of claim 1.

10. (currently amended) A method for detecting abnormalities occurring during a process based upon a continuously updated signature representative of the process, the method comprising:

continuously monitoring a system parameter;

computing a normal range of values for the system parameter based on the continuously updated signature;

determining if the monitored system parameter is within the normal range;

and

indicating existence of an abnormality if the monitored system parameter is outside of the normal range[[]],

wherein the process is related to usage of networked computing devices in a datacenter.

11. (Original) The method of claim 10, further comprising creating a signature by calculating an average and a standard deviation.

12. (Original) The method of claim 11, wherein creating a signature comprises accelerated learning through incrementally increasing a learning responsiveness ratio.

13. (Original) The method of claim 11, wherein creating a signature comprises initially repeating the running average and standard deviation through a plurality of intervals.

14. (Original) The method of claim 10, wherein computing a normal range of values comprises using a weighting factor to ensure that recently recorded data has a greater impact than older data.

15. (Original) The method of claim 10, wherein computing a normal range of values comprises utilizing a moving average over a time to account for events occurring at unexpected times.

16. (Original) The method of claim 10, wherein determining whether a monitored system parameter is within a normal range of values comprises determining if monitored system parameters are above an upper threshold or below a lower threshold.

17. (Original) The method of claim 16, further comprising calculating upper and lower threshold limits based on jitter offset.

18. (currently amended) A computer ~~readable~~storage medium having computer executable instructions for performing the method of claim 10.

19. (currently amended) A method for creating a signature useful for detecting abnormalities in a computing system environment, the method comprising:

setting a learning responsiveness ratio;

monitoring a system parameter;

adjusting the learning responsiveness ratio at fixed intervals until a desired value is reached;

calculating an average and standard deviation for each interval;

using the average, standard deviation and learning responsiveness ratio to create the signature[[]],

wherein the abnormalities in the computing system environment relate to usage of networked computing devices in a datacenter, and

wherein the signature includes information related to time sensitive averaging that accounts for variation in a business cycle.

20. (Original) The method of claim 19, further comprising continuously updating the created signature.

21. (Original) The method of claim 20, further comprising detecting abnormalities based on the updated signature.

22. (Original) The method of claim 19, wherein creating a signature comprises initially repeating the running average and standard deviation through a plurality of intervals.

23. (Original) The method of claim 20, wherein updating the created signature comprises using a weighting factor to ensure that recently recorded data has a greater impact than older data.

24. (Original) The method of claim 20, wherein updating the created signature comprises utilizing a moving average over a time to account for events occurring at unexpected times.

25. (Original) The method of claim 21, wherein detecting abnormalities comprises determining if measured values are above an upper threshold or below a lower threshold.

26. (Original) The method of claim 21, further comprising calculating upper and lower threshold limits based on jitter offset.

27. (currently amended) A computer readable storage medium having computer executable instructions for performing the method of claim 19.

28. (currently amended) A computerized system including computer storage medium for detecting abnormal activity in a computerized environment, the system comprising:
monitoring tools for continuously monitoring a system parameter;
a continuously updated signature representative of normal values of the system parameter; and

an abnormality indicator calculated based on the continuously updated signature, the abnormality indicator including a range of normal values for the system parameter[.],

wherein the abnormal activity is related to abnormal usage of networked computing devices in a datacenter, and

wherein the signature includes information related to time sensitive averaging that accounts for variation in a business cycle.

29. (Original) The system of claim 28, wherein the continuously updated signature comprises an average and a standard deviation.

30. (Original) The system of claim 28, wherein the continuously updated signature comprises a weighting factor to ensure that recently recorded data has a greater impact than older data.

31. (Original) The system of claim 28, wherein the continuously updated signature comprises a moving average over time to account for events occurring at unexpected times.

32. (Original) The system of claim 28, wherein the abnormality indicator determines whether a monitored system parameter is within a normal range of values and whether monitored system parameters are above an upper threshold or below a lower threshold.

33. (Original) The method of claim 28, wherein the abnormality indicator calculates upper and lower threshold limits based on jitter offset.

34. (currently amended) A computerized monitoring system including computer storage medium for monitoring a process, the monitoring system comprising:

a signature creation module for creating a signature representative of the process;

a signature updating module for continuously updating the created signature; and

an abnormality detection module for detecting abnormalities based upon deviations from the updated signature[.].

wherein the process is related to usage of networked computing devices in a datacenter, and

wherein the signature includes information related to time sensitive averaging that accounts for variation in a business cycle.

35. (Original) The system of claim 34, wherein the signature creation module includes tools for calculating an average and a standard deviation.

36. (Original) The system of claim 35, wherein the signature creation module comprises tools for performing accelerated learning through incrementally increasing a learning responsiveness ratio.

37. (Original) The system of claim 35, wherein creating a signature comprises initially repeating the running average and standard deviation through a plurality of intervals.

38. (Original) The system of claim 34, wherein the signature updating module comprises a weighting factor to ensure that recently recorded data has a greater impact than older data.

39. (Original) The system of claim 34, wherein the signature updating module comprises tools for calculating a moving average over a time to account for events occurring at unexpected times.

40. (Original) The system of claim 34, wherein the abnormality detection module determines if monitored system parameters are above an upper threshold or below a lower threshold.

41. (Original) The method of claim 34, wherein the abnormality detection module includes a mechanism for calculating upper and lower threshold limits based on jitter offset.

42. (currently amended) A method for distinguishing between normal and abnormal behavior during a process, the method comprising:

monitoring a system parameter;

converting a numeric data stream representative of the monitored system parameter to a state for the process;

distinguishing between normal and abnormal behavior based on the state[[]],

wherein the process is related to usage of networked computing devices in a datacenter,

wherein the system parameter includes at least one of a usage variable, utilization, an error, and turn around time, and

wherein distinguishing between normal and abnormal behavior includes utilizing time sensitive averaging to account for variation in a business cycle.

43. (Original) The method of claim 42, further comprising converting the numeric data streams to multiple sub-states.

44. (Original) The method of claim 42, further comprising determining a root cause of an abnormality based on the state.